

# TOTAL Hi-Perf 4T Special



TOTAL

## APPLICATIONS

- Specially designed to operate efficiently under extreme conditions , providing superior protection even in heavy traffic 'stop-n-go' conditions.
- Particularly recommended for all types of 4-stroke engine motorcycles.
- It is perfectly compatible with catalytic converters. The oil-change intervals recommended by the constructors and the minimum required viscosities must be complied with.
- This lubricant is compatible with lead-free fuels.

## PERFORMANCES

API SL  
JASO MA2

## CUSTOMER BENEFITS

Active prevention of friction

- Piston and ring sealing is ensured along with reduction of deposits. This leads to lower oil consumption and prevents loss of compression and loss of power. Thus the users get a smooth ride.

Superior gear protection

- Eliminates 'aeration' of lubricant by preventing foam formation and consequently avoid s early wear and tear.

HTHS viscosity

- the special additives in the oil stick for long to the gear parts preventing metal-to-metal contact under high pressure conditions and also during frequent gear changes.
- The oil formulation is certified with JASO MA2 specifications, thus preventing clutch slippage at start-up and varying speeds.
- The antiwear properties give the oil a High Temperature High Shear viscosity. This gives users ideal performance under extreme pressure conditions.
- Engine is protected by optimal maintenance of oil film thickness even in the most extreme load or speed conditions.

## CHARACTERISTICS

	Units	Method	SAE Grade
			15W40
Volumetric mass at 15°C	kg/m <sup>3</sup>	ASTM D1298	865
Viscosity at 100°C	mm <sup>2</sup> /s	ASTM D445	15.12
Viscosity at 40°C	mm <sup>2</sup> /s	ASTM D445	112.8
Viscosity Index	-	ASTM D2270	140
Flash Point	°C	ASTM D92	240
Pour Point	°C	ASTM D97	-30

*The values of the specifications shown in this table are typical values given as an indication only.*

TOTAL Hi-Perf 4T Special 15W-40  
Jan. 2014