

MOTOR OIL SAE 40



Monograde oil for Petrol & Diesel engine oil

UTILISATION

- Lubricant developed for Petrol and Diesel engines
- Every condition of use (city, highway, mountain, rough road)
- Designed for particular cars and/or utility vehicles before the year 1994 with a high mileage
- Miscible with other lubricants

PERFORMANCES

Specifications

API

SF/CD

CUSTOMER BENEFITS

- Stability of the on-stream oil
- Adapted levels of detergency and dispersivity
- Modern additivation technology, insuring the good functioning of engines

CHARACTERISTICS

TOTAL MOTOR OIL 40	Units	SAE Grade 40
Volumetric mass at 15°C	kg/m ³	898
Viscosity at 100°C	mm ² /s	15,5
Viscosity index	-	100
Flash Point	°C	>200
T.B.N	mgKOH/g	8.1

The typical characteristics mentioned represent mean values.

TOTAL OUTRE-MER
24, cours Michelet – La Defense 10
92069 PARIS LA DEFENSE
1/1

MOTOR OIL 40
September 2009
MKSP/LUB-MO40_01



This lubricant, when used according to our recommendations and for the purpose for which it is intended, presents no particular hazards.
A safety data sheet complying with current EC legislation can be obtained from your local commercial adviser.