



ELF HTX 3835 5W-30

100% synthetic lubricant for competition engines



"ELF HTX 38xx product range is considered by the racing motorists to be one of the very best racing lubricants in the world."

Uses

- **ELF HTX 3835** is a multigrade lubricant designed for 4-stroke engines.
- **ELF HTX 3835** is specially designed to obtain maximum engine power over short and/or very short runs.
- **ELF HTX 3835** is especially recommended for short, intense races where maximum performance is sought such as sprint circuit and qualifying races.
- Directly based on ELF experience in motorsport, **ELF HTX 3835** is particularly recommended for MotoGP, Superbike and Supersport engines.
- **ELF HTX 3835** is used for the following applications:
 - 4-stroke naturally-aspirated and turbocharged engines, up to 19,000 rpm and more
 - Motorcycle 4-stroke transmissions
- **ELF HTX 3835** is perfectly suited for competitions of short and very short duration:
 - Sprint circuit
 - Qualifying races
 - Hill climb races

Characteristics

	Typical values	Units	Methods
Density at 15°C	0.852	g/ml	NF EN ISO 12185
Viscosity at 40°C	72.27	mm ² /s	ASTM D-445
Viscosity at 100°C	12.36	mm ² /s	ASTM D-445
Viscosity HTHS	3.42	mPa.s	CEC L-036
Flash point	244	°C	NF EN ISO 2592



100% synthetic lubricant for competition engines

Properties

Characteristics	→	Technical gains	→	Engine benefits
Low viscosity (5W-30)	→	Serious reduction in frictional loss	→	Maximum power over entire speed range
Reversible high shear viscosity (HTHS)	→	Less energy wasted through viscous friction	→	Spontaneous power gain at high and very high speeds
Optimized formulation matrix	→	High de-airing capacity	→	Perfect lubrication of mechanical parts Greater compatibility with dry sump type technologies
Addition of specific frictional modifiers	→	Excellent lubrication at high and very high speeds	→	Maintains engine lubrication conditions to give maximum performance at high and very high speeds
detergency additive	→	Cleans and keeps clean all shells, pistons, segments	→	Maintains initial engine power perfectly
anti-wear additive	→	Adsorption on metal areas subject to very high pressure like tappets, cams and bearings	→	Greater engine protection with impeccable reliability
Dispersion surfactant	→	Carbonaceous matter kept in suspension	→	Reduces clogging of filters
Full synthetic , mineral base content strictly zero	→	Increase in thermal resistance	→	Reliability gain



100% synthetic lubricant for competition engines

ELF HTX 38xx

ELF HTX 3835 is miscible in any proportion with the whole 4-stroke engines lubricants ranges **ELF HTX 38xx** and **ELF HTX 8xx**.

ELF HTX 3820, **ELF HTX 3830** and **ELF HTX 3835** are primarily performance focused lubricants.

For long distance races, for greater protection, we recommend the **ELF HTX 8xx** range.

In the ELF HTX 38xx range, **ELF HTX 3835** is the most robust in terms of ultra fluid grade.

Recommendations

- **ELF HTX 3835** works perfectly up to 19,000 rpm.
- **ELF HTX 3835** is particularly suited to sprint races held over a weekend where the driving time does not exceed **four hours**.
- Due to its ultra fluid grade, it is recommended to carefully monitor mileage between each **ELF HTX 3835** oil change.
- No known incompatibility to date. Compatible in particular with silicon, fluorine, acrylic and nitrile type joints
- There is no specific precaution to take on first use of **ELF HTX 3835** other than removing the previous lubricant and replacing the oil filter.
- The use of an external additive (like engine remetalling) is not recommended.

Storage

To preserve its original properties, **ELF HTX 3835** must be handled and stored away from extreme weather conditions. The can must be carefully closed again after each use.

Glossary

For any further information relative to the technical aspects written in our Data Sheets, a glossary is on line on our website www.acs.total.com, racing fuels and lubricants section.

