



A brand of **TOTAL**

ELFMATIC CVT



High performance fluid for continuously variable transmission (CVT) of passenger cars

APPLICATIONS

- ELMATIC is recommended for RENAULT CVT Transmissions
- ELMATIC is recommended for JATCO CVT Transmissions
- **Do not use another CVT fluid for Renault Application**
- **Do not use this fluid for NISSAN CVT NS-1**
- This oil is compatible with NISSAN CVT NS-2

APPROVALS

Manufacturers' approval

Approved for RENAULT CVT **FK / CK / DK**

PERFORMANCES AND CUSTOMER BENEFITS

- Very good **thermal and oxidation stability**
- **Very high cold fluidity**
- Ensures very **good shifting** at all temperatures.
- Very **high resistance to shear**.
- **Protection** against wear

PHYSICAL AND CHEMICAL CHARACTERISTICS

ELFMATIC CVT		Method	Value
Density at 15°C	-	ASTM D1298	848
Kinematic Viscosity at 40°C	mm ² /s	ASTM D445	26
Kinematic Viscosity at 100°C	mm ² /s	ASTM D445	6.3
Viscosity Index	-	ASTM D2270	206
Flash point	°C	ASTM D92	175
Pour Point	°C	ASTM D97	-50

The features mentioned above are average values obtained with some variability in production and do not constitute a specification.