



A brand of **TOTAL**

ELF EVOLUTION 700 FT 10W-40



Premium multi-grade motor oil using ELF mineral technology, intended for lubricating gasoline passenger car engines

APPLICATIONS

Most recent technology engines

- Highest specification semi synthetic lubricant recommended for all high performance gasoline engine cars equipped with direct or indirect injection, multi valve and turbo-charge technologies

In all conditions

- Suitable for all conditions (in town, on highways or motorways); Meets needs of motor manufacturers regarding extended oil change intervals

Refer to the maintenance book of your vehicle to know the recommendation of the

PERFORMANCES

International specifications

API SN

CUSTOMER BENEFITS

Excellent engine protection

- Outstanding protection against wear

Optimal performance

- Advanced viscometrics for maximum power and minimum viscous drag
- Prevents sludge build-up and controls oxidation; Optimum power and performance under most severe driving conditions

CHARACTERISTICS

	Method	Units	SAE Grade 10W-40
Density at 15°C	ASTM D1298	Kg/m ³	866
Viscosity at 40°C	ASTM D445	mm ² /s	102
Viscosity at 100°C	ASTM 445	mm ² /s	14.7
Viscosity index	ASTM D2270	-	150
Pour point	ASTM D97	°C	-33
Flash point	ASTM D92	°C	238

The typical characteristics mentioned represent mean values

TOTAL LUBRIFIANTS – Immeuble Spazio
562, avenue du Parc de l'île
92029 Nanterre cedex
France

ELF EVOLUTION 700 FT 10W-40

Last update of this datasheet: 10/2015



This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.