



A brand of **TOTAL**

## TRANSELF NFP 75W-80



**Extreme-pressure lubricant of the Super High Performance (SHP) type for very highly stressed gearboxes. New Fuel Economy formulation**



### APPLICATIONS

- Synthetic technology lubricant for Renault vehicles equipped with P, J, NDX, TL4 family gearboxes
- TRANSELF NFP 75W-80 is especially recommended for easy gear changing in cold weather: also retains its outstanding qualities when hot, ensuring the smoothest possible operation and longer life for gearbox components.

### APPROVALS

|                                |  |
|--------------------------------|--|
| <b>Specifications</b>          | API GL-4+  |
| <b>Manufacturers' approval</b> | Officially approved and recommended by RENAULT for PXX, JXX, NDX, TL4 gearboxes<br>Nissan P gearboxes. |

### PERFORMANCES AND CUSTOMER BENEFITS

#### Easy driving by any weather

- Advanced protection for synchro components.
- Outstanding resistance to shear.
- Extreme-pressure and anti-wear capabilities enabling gears to function under the most severe stresses.
- Unrivalled thermal performance, guaranteeing a stable product even under heavy loads and at high temperature.

#### Operation under heavy load

- Particularly stable coefficient of friction ensuring satisfactory synchronisation in all conditions.
- High viscosity index and low pour point ensuring perfect lubrication at all temperatures.

#### Long lifetime of the gearbox

- Outstanding rust control and anticorrosion properties.
- Very high antifoaming power.
- Inert to seals.

### PHYSICAL AND CHEMICAL CHARACTERISTICS

#### TRANSELF NFP 75W-80

|                              |                    | Method     | Value |
|------------------------------|--------------------|------------|-------|
| Density at 15°C              | --                 | ASTM D1298 | 868   |
| Kinematic Viscosity at 40°C  | mm <sup>2</sup> /s | ASTM D445  | 36    |
| Kinematic Viscosity at 100°C | mm <sup>2</sup> /s | ASTM D445  | 8.5   |
| Flash point                  | °C                 | -          | 192   |
| Viscosity Index              | -                  | ASTM D2270 | 187   |
| Pour Point                   | °C                 | ASTM D97   | -51   |

*The features mentioned above are average values obtained with some variability in production and do not constitute a specification.*