



A brand of **TOTAL**

EVOLUTION 500 FTX 10W-30



Premium multi-grade motor oil using ELF mineral technology, intended for lubricating gasoline passenger car engines



APPLICATIONS

- Most recent technology engines**
- Premium multi-grade motor oil for all engines, recommended for all high performance gasoline engine cars equipped with direct or indirect injection, multi valve and turbo-charge technologies
- In all conditions**
- Suitable for all conditions (in town, on highways or motorways); Meets needs of motor manufacturers regarding extended oil change intervals

Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer

PERFORMANCES

- International Specifications**
- API SN/CF; ILSAC GF-5

CUSTOMER BENEFIT

- Fuel Economy**
- Promoted fuel saving
- Excellent engine protection**
- Excellent start-up performance, prevents sludge build-up and controls oxidation
- Optimum performance**
- Optimum power and performance under most severe driving conditions
- Low emission vehicle**
- Fully compatible with all emission control devices

CHARACTERISTICS

EVOLUTION 500 FTX 10W-30	Method	Units	SAE Grade 10W-30
Density at 15°C	ASTM D1298	Kg/m ³	868
Viscosity at 40°C	ASTM D445	mm ² /s	67
Viscosity at 100°C	ASTM 445	mm ² /s	10
Viscosity index	ASTM D2270	-	128
Pour point	ASTM D97	°C	-33
Flash point	ASTM D92	°C	234

The typical characteristics mentioned represent mean values