



A brand of **TOTAL**

EVOLUTION 900 FT 5W-50



Top performance motor oil using ELF fully synthetic technology, intended for lubricating gasoline passenger car engines

APPLICATIONS

Most recent technology engines

- Recommended for all high performance gasoline engine cars equipped with direct or indirect injection, multi-valve and turbo-charge technologies

Even in very severe conditions

- Suitable for protection under severe driving style or conditions
- Stability and endurance under severe conditions(heat, load, speed)that can cause conventional oils to break down

Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer

PERFORMANCES

International Specifications

- API SN/CF

CUSTOMER BENEFIT

Excellent engine protection

- Protects moving parts even at very high operating temperatures

Optimal performance

- Extended oil change intervals; Thermal resistance and reliability gain; Excellent start-up performance and prevents sludge build-up and controls oxidation
- Keeps engine clean for consistent engine power output

CHARACTERISTICS

EVOLUTION 900 FT 5W-50	Method	Units	SAE Grade 5W-50
Density at 15°C	ASTM D1298	Kg/m ³	854
Viscosity at 40°C	ASTM D445	mm ² /s	129
Viscosity at 100°C	ASTM 445	mm ² /s	19.5
Viscosity index	ASTM D2270	-	173
Pour point	ASTM D97	°C	-36
Flash point	ASTM D92	°C	249

The typical characteristics mentioned represent mean values