



## Transmission Fluid for Automatic Gearbox and Power Steering Systems

### APPLICATIONS

**Automatic Gearbox**

**Power-Shift Transmission**

**Power Steering**

- Recommended for use in automatic transmission and power-shift systems where a DEXRON II or III fluid is recommended such as :
  - Automatic gearboxes
  - Hydraulic clutches
  - Power-assisted steering systems
  - Power-shift transmission

Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer

### PERFORMANCES

**Meet the OEM specifications**

- GM DEXRON III G
- FORD MERCON
- ZF TE ML 14A

### CUSTOMER BENEFITS

**Optimum drain interval**

**Smooth Gear Shifting**

**Outstanding desired fluid properties**

**Excellent elastomers compatibility**

- Excellent thermal stability and oxidation resistance to maintain an efficient operation over the recommended drain interval
- Unique friction properties to provide lasting gear shifting without shudder
- Outstanding oxidation stability, shear strength, foaming property, rust protection and resistance to wear and corrosion guarantee extended protection to gearbox
- Proven compatibility with elastomers(seals) to prevent oil leakage

### CHARACTERISTICS

Test Description	Method	Units	ELFMATIC III G
Colour	VISUAL	--	RED
Density at 15°C	ASTM D4052	Kg/m3	851
Viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	34
Viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	7.3
Viscosity index	ASTM D2270	-	185
Pour point	ASTM D97	°C	-48
Flash point	ASTM D92	°C	220

The typical characteristics mentioned represent mean values