



TOTAL QUARTZ 9000 0W-30

Engine oil

KEY DATA

LIGHT VEHICLE RANGE



PETROL AND DIESEL ENGINE OIL

SAE 0W-30

SYNTHETIC TECHNOLOGY

FUEL ECONOMY

INTERNATIONAL STANDARDS

- ✓ ACEA A5/B5
- ✓ API SL/CF

MANUFACTURER APPROVALS AND PERFORMANCE LEVELS

- ✓ VOLVO VCC 95200377
- ✓ Suitable for FORD

APPLICATIONS

TOTAL QUARTZ 9000 0W-30 is synthetic technology engine oil that has been developed to cover the most stringent requirements of both gasoline and diesel passenger cars engines. TOTAL QUARTZ 9000 0W-30 is particularly suited to the most recent engines.

This engine oil can be used in the most difficult operating conditions (city traffic, major roads, motorways), and is appropriate for all driving types, especially sporty, high-speed and all-season driving.

CUSTOMER BENEFITS

- **Anti-wear protection:** this oil ensures optimum engine longevity with its anti-wear properties that protect the engine's most sensitive parts.
- **Extended oil change intervals**
- **Engine protection, cleanliness and performance:** This oil contains detergent and dispersive additives that keep the engine clean, high performing and thus preserve its power.
- **Easier cold starts:** its exceptional fluidity is perfectly adapted for cold starting in extreme weather conditions and ensures a good protection of mechanical parts at high temperature.
- **Reduced friction:** Its outstanding fluidity reduces friction and therefore creates significant fuel savings (Fuel Economy was measured at 2.6% during official M111FE testing) and reduces CO2 emissions.

CHARACTERISTICS*

Test	Unit	Test method	Result
SAE Grade		SAE J 300 E	0W-30
Viscosity at 40°C	mm ² /s	ASTM D445	54.2
Viscosity at 100°C	mm ² /s	ASTM D445	10.2
Viscosity Index	-	ASTM D2270	180
B.N.	mgKOH/g	ASTM D2896	9.7

* The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations.

If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet. This can be obtained on request from your local reseller and is available for consultation at www.quickfds.fr.

This product should not be used for any purposes other than the ones for which it is intended.

When disposing of the product after use, please protect the environment and comply with local regulations.