



DYNATRANS AC 60



TOTAL

Lubricant for machinery axles equipped with specific oil immersed brake discs.

APPLICATIONS

**Axle
Final drives**

Very hot climates

- Lubrication of axles and final drives which require an oil meeting the CATERPILLAR TO-4 specification.
- The SAE 60 viscosity grade is suitable when the ambient temperature exceeds 40°C.

PERFORMANCES

Meets manufacturers' specifications

Suitable for transmission systems

CATERPILLAR : TO-4

DANA, EATON FULLER, KOMATSU, ROCKWELL...

CUSTOMER BENEFITS

Security

Long component life

- Good resistance to the temperature
- Excellent antiwear and anticorrosion properties
- Good performance with respect to seals
- Friction properties adapted to the types of equipment referenced

SPECIFICATIONS

DYNATRANS AC	Units	60
Viscosity at 40°C	mm ² /s	318
Viscosity at 100°C	mm ² /s	24
Viscosity index		96
Pour point	°C	- 9

The values of the specifications shown in this table are typical values given as an indication only.

TOTAL LUBRIFIANTS
562 avenue du Parc de l'Île
92029 NANTERRE
France

DYNATRANS AC 60
Sheet updated : 09/2010



This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.