



# MULTAGRI SUPER 15W-40



**TOTAL**

Multipurpose lubricant intended for lubrication of different systems of agricultural machineries

## APPLICATIONS

**Agriculture**  
**Mechanical components and systems in agricultural machinery**

- Atmospheric or supercharged diesels, petrol service motors.
- Mechanical transmissions, gearboxes, reduction drives, bevel gears, for which an oil type API GL4 / MIL.L.2105 SAE 80W-90 is recommended.
- Mechanical transmissions fitted with oil bath brakes.
- Hydraulic lift and assistance circuits.
- Power take-offs and multidisc clutches operating in oil.
- Hydrostatic steering systems.

## PERFORMANCES

**Classifications**  
**Manufacturer approvals**  
**Meets manufacturer specifications**

- ACEA E2 -- API CF-4/CE/SF
- MASSEY-FERGUSON : CMS M 1145 ; CMS M 1144  
ZF : TE-ML 06B / 07B
- **Engine applications** : FORD M2C 159B3, MASSEY FERGUSON CMS M1139, JOHN DEERE JDM J27
  - **Transmission applications** : JOHN DEERE JDM J20A, J20C, FORD M2C86A, M2C134D, FNHA 2 C 201.00, MASSEY FERGUSON CMS M1127A, M1135
  - **Gear applications** : API GL4
  - **Automatic transmission applications** : GM ALLISON C4

## CUSTOMER BENEFITS

**Rationalisation**  
**Protects the engine, transmission components and hydraulic systems**

- Reduces the number of lubricants needed on a farm.
- High viscosity when hot, ensuring continuous lubrication in the engine and on gears and hydraulic components.
- Outstanding wear control ensuring long life for the engine, transmission systems and hydraulic circuit components.
- Extreme-pressure capability allowing lubrication of transmissions that require the use of an oil type API GL4 or MIL.L.2105 of viscosity SAE 80W-90.
- Anti-corrosion properties to protect the non-ferrous metals in the engine and other systems.
- Excellent anti-foaming properties, to prevent any sump overflow as well pump depriming or cavitation.
- Completely inert to seals.
- Special frictional characteristics ensuring progressive, efficient and silent operation of brake and clutch systems.

## CHARACTERISTICS

MULTAGRI SUPER	Unités	15W-40
Kinematic viscosity at 40°C	mm <sup>2</sup> /s (cSt)	99
Kinematic viscosity at 100°C	mm <sup>2</sup> /s (cSt)	13.4
Viscosity index		137
Pour Point	°C	-39

*The characteristics shown in this table are typical values provided for illustrative purposes.*

TOTAL LUBRIFIANTS  
562 avenue du Parc de l'île  
92029 NANTERRE  
FRANCE

**MULTAGRI SUPER 15W-40**  
Sheet updated : 01/2013



This lubricant, when used according to our recommendations and for the purpose for which it is intended, presents no particular hazard. A safety data sheet complying with current EC legislation can be obtained from your local sales representative.