



Innovation
that excites

NISSAN MOTOR OIL FULL SYNTHETIC 5W30 SN/GF-5

High Performance Synthetic Technology Gasoline/Petrol Engine Oil

USES

- Recommended for Nissan Gasoline/Petrol Engines requiring an SAE 5W-30 motor oil
- Recommended for modern Nissan Gasoline/Petrol Engines, particularly HR12DDR, HR12DE and MR16DDT models
- Designed for use in demanding driving conditions including city, country and motorway
- Engineered for use in all climates
- Refer to your vehicle's Owner's Manual or Nissan Workshop Manual for refill and maintenance schedules

PERFORMANCE

NISSAN MOTOR OIL FULL SYNTHETIC 5W-30 SN/GF-5 meets or exceeds the requirements of:

- API: SN
- ILSAC GF-5

CUSTOMER BENEFITS

- Optimal engine cleanliness
- Exceptional thermal stability and oxidation resistance
- Sustained engine component protection
- Outstanding fuel economy enhancement
- Minimised harmful exhaust emissions

CHARACTERISTICS

	Method	Units	SAE Grade 5W30
Density at 15°C	ASTM D1298	kg/m ³	852
Viscosity at 40°C	ASTM D445	mm ² /s	56
Viscosity at 100 °C	ASTM D445	mm ² /s	10
Viscosity index	ASTM D2270	-	170
Pour Point	ASTM D97	°C	-36
Flash Point	ASTM D92	°C	230
T.B.N.	ASTM D2896	mgKOH/g	10

This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute a special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.

The typical characteristics mentioned represent mean values