

## TOTAL FINADET HD

### Caustic Based Degreaser

#### KEY DATA

**Concentrated water based** caustic degreaser ideal for heavy duty industrial, agricultural and workshop cleaning.

#### Recommended Dilution Ratios and use:

- Apply liberally to the surfaces to be cleaned with a spray or brush. Allow to stand for 5 minutes then rinse.
- **Concrete Cleaning** – apply direct to concrete and allow 2 to 3 minutes to soak in, scrub with a yard broom and then rinse off with water.
- Heavy Soils – Use undiluted
- Medium Soils – 1:4
- Light Soils – 1:10
- Pressure Washers – 1:100 (Ensure pressure washer can tolerate high pH cleaners).

**IMPORTANT:** In the presence of unprotected magnesium, magnesium alloys or polished aluminium it is recommended to wet the surfaces with water prior to applying the diluted mix of water and FINADET HD. Reduce both contact time and concentration of FINADET HD for this application.

#### Customer benefits

- ✓ **FINADET HD** is ideal for the cleaning of a broad range soiling and is excellent for soaking through thick layers of clay, grease, foodstuffs and oil stains.
- ✓ **Non Flammable** so suitable for use in areas where flammable liquids cannot be used.
- ✓ **Excellent Adhesion and Cleaning Ability** enable FINADET HD fast and long term cleaning with minimal degradation of surfaces.
- ✓ **Effectively Removes Road Grime and Dirt** from all surfaces including plastic, rubber, chrome, aluminium and paintwork.
- ✓ **FINADET HD** will not damage wires and hoses in engine compartments but it is not suitable for painted surfaces.

---

## Characteristics\*

---

Test	Result
Appearance	Clear Yellow Liquid
Odour	Moderate Odour
pH (concentrate)	12.3
Flammable	Non Flammable
Boiling Point	80 - 150°C
Solubility	Soluble in Water
Specific Gravity	0.98 - 1.02
ADG Code	Class 8 Corrosive

---

\* The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

## Recommendations for use

---

Before using the product, the vehicle's maintenance guide should be checked.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations.

If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

## Health, safety and the environment

---

Please refer to the Material Safety Data Sheet for full safety information. This can be obtained on request from your local reseller and is available for consultation at [www.totaloil.com.au](http://www.totaloil.com.au).

This product should not be used for any purposes other than the ones for which it is intended.

When disposing of the product after use, please protect the environment and comply with local regulations.