

TOTAL FINADET TW

Water based, non caustic, heavy duty truck wash
Biodegradable and streak free

KEY DATA

Concentrated water based high performance non caustic truck wash.

Biodegradable formulation.

Quick Break formulation: readily separates water and oil.

FINADET TW is primarily used to wash trucks, trailers, cars, boats, coaches and mining equipment.

FINADET TW is suitable for use in pressure washers and automated washing systems.

FINADET TW is also very effective as a floor cleaner and laundry cleaner, especially on greasy clothing.

Recommended Dilution Ratios for use:

- Light cleaning, and general washing. 1:50
- Medium cleaning, dirt and grime. 1:25
- Heavy cleaning, built up dirt and stubborn road grime. 1:5
- Floor cleaning. 1:50
- Laundry cleaner including greasy overalls. 1:25

Customer benefits

- ✓ **Effectively Removes Road Grime and Dirt** from all surfaces including plastic, rubber, chrome, aluminium and paintwork.
- ✓ **Non Streak Formula:** Specifically developed not to streak leaving paintwork shiny and streak free.
- ✓ **Rationalise cleaners:** FINADET TW can be used for trucks, trailers, side curtains, cars, boats, coaches and mining equipment as well as all fabrics found in the transport and marine environments. FINADET TW is also effective as a floor and laundry cleaner making it a true multiservice cleaner.
- ✓ **Anti-corrosion:** Being Non Caustic and containing corrosion inhibitors FINADET TW protects against rusting and corrosion.
- ✓ **Economical to Use:** Can be used across a broad range of dilutions dependant on the performance required to control costs.

Characteristics*

Test	Result
Appearance	Light Blue Liquid
Odour	Very slight Odour
pH (concentrate)	7.5
Flammable	Non Flammable
Melting Point	-4°C
Boiling Point	121°C
ADG Code	Non Dangerous
Solubility	Soluble in Water
Specific Gravity	1.075

* The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

Recommendations for use

Before using the product, the vehicle's maintenance guide should be checked.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations.

If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

Health, safety and the environment

Please refer to the Material Safety Data Sheet for full safety information. This can be obtained on request from your local reseller and is available for consultation at www.totaloil.com.au.

This product should not be used for any purposes other than the ones for which it is intended.

When disposing of the product after use, please protect the environment and comply with local regulations.