

BLUE CONCENTRATE



Lubrication

Blue dye for hydraulic circuit.

APPLICATIONS

Hydraulic circuit

- Useful for all hydraulic circuit.
- Adding of this coloring additive to an hydraulic oil give it a blue color. Don't use **BLUE CONCENTRATE** for aqueous solutions.
- The proportioning may change, according to the requirement, from 0,2 to 1% in the hydraulic oil.

ADVANTAGES

The adjonction of the **BLUE CONCENTRATE** additive allows:

- To avoid a confusion with motor oil.
- A quicker detection of possible leakages.
- An easy identification of the lubricant.
- An easy reading of the lubricant gauge level.

HANDLING HYGIENE - SAFETY

- **BLUE CONCENTRATE** fulfils the RENAULT 00-10-050/D safety specifications.
- Non toxicity of the additive.
- No labelling.
- High flash point.

TYPICAL CHARACTERISTICS	METHODS	UNITS	BLUE CONCENTRATE
Aspect	Visual	-	Opaque
Colour	ASTM D 1500	-	Blue
Specific gravity at 15°C	ASTM D 1298	kg/m ³	859
Viscosity at 40 °C	ASTM D 445	mm ² /s	16.5
Flash point OC	NF T 60 118	°C	209

Above characteristics are mean values given as an information.