

CHAINLUB



Spray



Lubricant for chains, cables and different mechanisms.

APPLICATIONS

Aerosol

Chain Lubrication

- Lubrication of chain from industrial devices in textil or printing industries or in forklift trucks.
- Winch, crane and brake cables lubrication.
- Joint and various mechanisms : locks, hinges, wipers bearings, dynamos, alternators, domestic devices...
- Hard to reach applications.

ADVANTAGES

- Strong stickiness thanks to dedicated additives.
- High penetrating power.
- Good oxidantion resistance.
- Anticorrosion properties improved.

TYPICAL CHARACTERISTICS	METHODS	UNITS	CHAINLUB
Density at 15 °C	ISO 3675	kg/m ³	821
Viscosity at 40 °C with solvent	ISO 3104	mm ² /s	5
Viscosity at 40 °C without solvent	ISO 3104	mm ² /s	68
Flash Point	ISO 2719	°C	> 56

Above characteristics are mean values given as an information.

CAUTION

Due to the container and the presence of solvents :

- Keep away from heat, sparks and flame.
- Do not expose to heat and temperatures exceeding 50°C.
- Even when empty, do not puncture or incinerate container.



TOTAL LUBRIFIANTS
Industrie & Spécialités
10-10-2006
CHAINLUB



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.
A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded from www.quick-fds.com.