

OSYRIS DWX 7000



Metalworking

UTILISATIONS

- **OSYRIS DWX 7000** is a dewatering and protective fluid.
- In addition, **OSYRIS DWX 7000** coats the surface with a fatty soft film to give a long-term protection during outdoor sheltered storage.
- **OSYRIS DWX 7000** complies with standard ISO 6743/8 (1987) : REE category.

ADVANTAGES

- **OSYRIS DWX 7000** is widely recommended for use the metal industry or after a surface treatment.
- Good water-repellent capability.
- **OSYRIS DWX 7000** deposits a fatty soft protective film.
- Protection guaranteed during 18 months in case of indoor storage and 12 months in case of outdoor storage under rain-shelter.
- **OSYRIS DWX 7000** may be applied:
 - by dipping,
 - by spraying,
 - by brushing.
 - The film may be eliminated by:
 - alkaline detergent
 - solvents (liquid or vapour phase).

| TYPICAL CHARACTERISTICS | METHODS | UNITS | OSYRIS DWX 7000 |
|------------------------------|------------|--------------------|-----------------|
| Appearance | visual | - | liquid |
| Colour | visual | - | Dark red |
| Specific gravity at 15 °C | ISO 3675 | kg/dm ³ | 0.850 |
| Kinematic viscosity at 20 °C | ISO 3104 | mm ² /s | 10 |
| Kinematic viscosity at 40 °C | ISO 3104 | mm ² /s | 6 |
| Flash point | ISO 2719 | °C | 38 |
| Pour point | ISO 3016 | °C | - 20 |
| Water displacement power | IP 178 (B) | value | yes |

Above characteristics are mean values given as an information.

TOTAL LUBRIFIANTS
Industrie & Spécialités

27 august 2001

OSYRIS DWX 7000

1/1

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded from

www.quick-fds.com.

