



EXCELLIUM FT 5W-40



Top performance Motor oil using ELF fully synthetic technology. Intended for lubricating passenger cars Gasoline and Diesel engines.

APPLICATIONS

Most recent technology engines

The most severe journeys

« Vigorous » driving, all times of year

- Suitable for all gasoline engine(particularly for most recent ones) and diesel
- Suitable for all journeys (in town, on highways and motorways) and particularly in severe conditions.
- Meets the needs of the car manufacturers regarding extended oil change intervals.

Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer.

PERFORMANCES

International specifications

API: SN
API CF performance level

CUSTOMER BENEFITS

Optimal performance

engine protection

Facilitates cold starts

- Excellent engine protection, particularly against timing system wear
- Provides for extra long intervals between oil changes
- Outstanding thermal stability and oxidation resistance ensuring prolonged engine life
- Facilitates ignition in very cold weather and maintains protection in great heat

CHARACTERISTICS

ELF EXCELLIUM FT 5W-40	Method	Units	SAE Grade 5W-40
Viscosity at 40°C	ASTM D445	mm ² /s	90
Viscosity at 100°C	ASTM D445	mm ² /s	14.3
Viscosity Index	ASTM D2270	-	166
Pour Point	ASTM D97	°C	-33
Flash Point	ASTM D92	°C	243
B.N.	ASTM D2896	mgKOH/g	7

The typical characteristics mentioned represent mean values

