

TANKER CALIBRATION CHART

TANK CALIBRATED BY COAST INSTRUMENT & PUMP ENGINEERS.

(On Horse Benz KBS 203 J)

VEHICLE OWNED BY: A.O. Bayusuf & Sons Ltd.
MAKE AND REGISTRATION No. Semi Trailer ZC 9566

P.O. BOX 86086
PHONE: 0725 944469
MOMBASA

183.85 COMPARTMENT (1)		206.2 Compartment (2)		206.25 COMPARTMENT (3)	
DIP CM	CAPACITY CU. METER	Dip Cm.	Capacity Cu.Meter	DI CM	CAPACITY CU. METER
15.65	1.00	20.2	1.00	23.2	1.00
28.3	2.00	32.5	2.00	37.3	2.00
39.55	3.00	43.5	3.00	50.35	3.00
50.25	4.00	53.95	4.00	62.95	4.00
61.15	5.00	64.35	5.00	75.5	5.00
71.55	6.00	75.0	6.00	88.0	6.00
82.15	7.00	84.8	7.00	100.2	7.00
92.65	8.00	94.95	8.00	112.65	8.00
		105.1	9.00		
103.3	9.00	115.5	10.00	125.5	9.00
113.85	10.00	125.3	11.00		
124.6	11.00	135.8	12.00	137.75	10.00
135.9	12.00	146.1	13.00	150.8	11.00
148.75	13.00	156.7	14.00	164.45	12.00
157.0	13.50	168.15	15.00	181.15	13.00
163.8	13.75	182.75	16.00	186.9	13.25

CALIBRATION CHARTS WITH APPROPRIATE DIP STICKS ARE THE GUIDANCE FOR LOADING AND OFF-LOADING PRODUCTS AT BONDED OIL INSTALLATIONS. METER WHICH IS CALIBRATED AND SEALED BY THE WEIGHTS & MEASURES DEPARTMENT BE USED TO VERIFY.

N.B. Line "T."T. MUST be Level with tube top when taking dip.

Volume based at 20°C.

21/10/2016 (U.M) 6523

