

TANKER CALIBRATION CHART

TANK CALIBRATED BY COAST INSTRUMENT & TANK ENGINEERS.

(On Horse Base KCC 065 H)

VEHICLE OWNED BY: A.O. Bayusuf & Sons Ltd.
MAKE AND REGISTRATION No. Semi Trailer ZB 1510

P.O. BOX 86086-80100
PHONE: 0725 944469
MOMBASA

169.45

COMPARTMENT (1)

DIP CM	CAPACITY CU. METER
21.3	0.50
35.2	1.00
48.1	1.50
59.6	2.00
71.45	2.50
83.15	3.00
94.85	3.50
107.05	4.00
119.1	4.50
132.4	5.00
143.25	5.25

170.8

Compartment (2)

Dip Cm.	Capacity Cu. Meter
19.0	0.25
31.2	0.50
41.95	0.75
52.15	1.00
62.45	1.25
72.35	1.50
82.2	1.75
91.7	2.00
101.5	2.25
111.75	2.50
122.15	2.75
133.4	3.00
148.7	3.25

170.25

COMPARTMENT (3)

DI CM	CAPACITY CU. METER
23.8	0.25
39.85	0.50
54.6	0.75
69.25	1.00
83.35	1.25
97.75	1.50
112.65	1.75
128.25	2.00
149.15	2.25

169.95

Compartment (4)

Dip Cm.	Capacity Cu. Meter
18.25	0.25
30.3	0.50
41.2	0.75
51.4	1.00
61.65	1.25
71.6	1.50
81.4	1.75
91.2	2.00
101.35	2.25
111.6	2.50
122.05	2.75
133.7	3.00
149.5	3.25

170.55

Compartment (5)

Dip Cm.	Capacity Cu. Meter
18.35	0.25
30.45	0.50
41.1	0.75
51.45	1.00
61.25	1.25
71.55	1.50
81.25	1.75
90.95	2.00
101.0	2.25
111.1	2.50
121.7	2.75
133.15	3.00
148.1	3.25

169.95

Compartment (6)

Dip Cm.	Capacity Cu. Meter
22.8	0.50
37.75	1.00
51.2	1.50
64.3	2.00
76.55	2.50
89.25	3.00
101.8	3.50
115.25	4.00
129.4	4.50
149.15	5.00

CALIBRATION CHARTS WITH APPROPRIATE DIP STICKS ARE THE GUIDANCE FOR LOADING AND OFF-LOADING PRODUCTS AT BONDED OIL INSTALLATIONS. METER WHICH IS CALIBRATED AND SEALED BY THE WEIGHTS & MEASURES DEPARTMENT BE USED TO VERIFY.

N.B. Line "T." MUST be Level
with tube top when taking dip.
Volume based at 20°C.
95/03/2018 (U.M) 7578

