

TANKER CALIBRATION CHART

TANK CALIBRATED BY COAST INSTRUMENT & PUMP ENGINEERS.

(On Horse Benz KCC 069 H)

VEHICLE OWNED BY: A.O. Bayusuf & Sons Ltd.
MAKE AND REGISTRATION No. Semi Trailer ZE 6112

P.O. BOX 86086
PHONE: 0725 944469
MOMBASA

155.6
COMPARTMENT (1)

DIP CM	CAPACITY CU. METER
17.25	0.50
29.6	1.00
41.35	1.50
52.95	2.00
63.6	2.50
74.15	3.00
84.35	3.50
95.3	4.00
100.45	4.25
105.95	4.50
111.55	4.75
117.25	5.00

155.6
Compartment (2)

Dip Cm.	Capacity Cu. Meter
16.1	0.25
27.85	0.50
38.65	0.75
49.1	1.00
59.05	1.25
68.8	1.50
78.85	1.75
88.4	2.00
98.0	2.25
108.2	2.50
118.65	2.75
129.2	3.00

155.4
COMPARTMENT (3)

DI CM	CAPACITY CU. METER
21.9	0.25
38.8	0.50
53.35	0.75
68.2	1.00
83.15	1.25
97.9	1.50
113.4	1.75
129.6	2.00

154.8
Compartment (4)

Dip Cm.	Capacity Cu. Meter
20.5	0.25
32.25	0.50
43.5	0.75
53.9	1.00
64.3	1.25
74.75	1.50
84.4	1.75
94.3	2.00
104.55	2.25
114.75	2.50
125.35	2.75
136.5	3.00

155.65
Compartment (5)

Dip Cm.	Capacity Cu. Meter
19.4	0.25
30.75	0.50
41.6	0.75
52.05	1.00
61.85	1.25
71.7	1.50
81.55	1.75
91.0	2.00
101.3	2.25
111.3	2.50
121.65	2.75
132.5	3.00

154.9
Compartment (6)

Dip Cm.	Capacity Cu. Meter
22.05	0.50
38.05	1.00
53.65	1.50
68.45	2.00
83.1	2.50
98.0	3.00
104.95	3.25
112.45	3.50
120.55	3.75
128.65	4.00

CALIBRATION CHARTS WITH APPROPRIATE DIP STICKS ARE THE GUIDANCE FOR LOADING AND OFF-LOADING PRODUCTS AT BONDED OIL INSTALLATIONS. METER WHICH IS CALIBRATED AND SEALED BY THE WEIGHTS & MEASURES DEPARTMENT BE USED TO VERIFY.

N.B. Line "T."T. MUST be Level with tube top when taking dip.

Volume based at 20°C.

16/01/2016 (U.M) 5830

Plen
16 JAN 2016

