

FINATUROL HT



Food processing aid



Vegetable demoulding oil for high temperatures.

APPLICATIONS

Bakery and pastry

- **FINATUROL HT** is a vegetable demoulding oil. It is used for severe moulding operations after they have come out of the oven.
- **FINATUROL HT** guarantees a perfect demoulding operation for all bakery and pastry products and it respects the taste and odor of the finished product even for products with a long shelf life.
- The film is maintained during the baking of the products. It ensures excellent demoulding performances and it prevents sticking.

SPECIFICATIONS

Food processing aid:

- 100% vegetable
- GMO free
- Allergen free
- NSF 3H registered
- DGCCRF approved

- **FINATUROL HT** is a **100% vegetable** oil guaranteed **GMO free** and made **without animal products**. It is a mixture of vegetable oils and food additives which are included in the positive list of the European directive 95/2/CE.
- **FINATUROL HT** meets the international laws concerning food processing aids. Its use is subjected to the applicable laws and regulations in each country.
- It may be used in direct contact with food according to USA FDA CFR 182-184
- **FINATUROL HT** complies with 1829/2003/CE and regulations related to the labeling of GMO (GMO free).
- **FINATUROL HT** is free of food allergens in compliance with 2000/13/CE and 2003/89/CE.

ADVANTAGES

Reducing the maintenance costs and extending the life of the moulds

Reducing oil consumption

Tasteless and odorless

Easy to apply

- Due to its excellent resistance to oxidation, **FINATUROL HT** prevents deposit formation, thus reducing the cleaning frequency. It extends the life of the equipments and of the mould coating.
- **FINATUROL HT** allows to significantly reduce oil consumption (up to 40%) in comparison to conventional demoulding agents (vegetable or white mineral oils).
- Due to its specific formula, **FINATUROL HT does not change the taste nor the odor of the finished product.**
- **FINATUROL HT** is a homogeneous liquid which doesn't require pre-heating. Its viscosity allows the customer to use it in a spraying system without heating it.

TYPICAL CHARACTERISTICS	METHODS	UNITS	FINATUROL HT
Aspect, color	Visuelle	-	Clear yellow liquid
Density at 20 °C	NF EN ISO 12185	kg/m ³	930
Viscosity 40°C	NF EN ISO 3104	mm ² /s	110

Above characteristics are mean values given as an information.

Recommendations :

- Store between 0°C and 30°C in a place protected from day light - Shelf life: 9 months from date of manufacture.

TOTAL LUBRIFIANTS
Industrie & Spécialités
13-06-2012 (supersedes 18-07-2007)
FINATUROL HT
1/1



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.
A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded from www.quick-fds.com.